

**REAL.  
COOL.  
COLORS.**

PREMIER

**RADIANCE™**

*Solar Reflective Shingles*



PABCO® Roofing Products



RADIANCE 50 GLACIER  
0.25 Initial Solar Reflectance



RADIANCE 50 MADRONA  
0.25 Initial Solar Reflectance



RADIANCE 50 PEBBLE  
0.25 Initial Solar Reflectance



RADIANCE 30 SNOWCAP  
0.28 Initial Solar Reflectance



RADIANCE 50 OBSIDIAN  
0.20 Initial Solar Reflectance



RADIANCE 50 ALDER AR †  
0.26 Initial Solar Reflectance



RADIANCE 50 PEBBLE AR †  
0.26 Initial Solar Reflectance



RADIANCE 30 SNOWCAP AR †  
0.28 Initial Solar Reflectance

## WHY COMPROMISE?

PREMIER Radiance™ Shingles meet California Title 24 requirements for initial and aged solar reflectance without compromising on color choices. Contact your local PABCO® distributor or installer for pricing and availability.

### RADIANCE 50 FEATURES

- Transferable 50 Year Limited Warranty\*
- 90 mph Limited Wind Warranty
- Weight Per Square 320 lbs. (nominal)

### RADIANCE 30 FEATURES

- Transferable 30 Year Limited Warranty\*
- 70 mph Limited Wind Warranty
- Weight Per Square 260 lbs. (nominal)

\*See PABCO®'s Limited Shingle Warranty for details, limits and conditions.

† Algae Resistant (AR) Shingles are warranted against algae growth for 10 years. AR Shingles are not available in all markets.

### TECHNICAL INFORMATION

UL Classified To Meet:

- ASTM D3462 Fiberglass Shingle Standard
- ASTM D3161 Class F, Wind Resistance Standard
- UL 997 at 110 mph
- UL 790 Class A, Fire Resistance Standard
- UL 2218 Class 3 Impact Resistance (Radiance 50 only)
- CAN/ULC-S107

Complies With:

- ASTM D3018 Type I
- CSA Fiberglass Shingle Standard A123.5

 <small>COOL ROOF RATING AGENCY</small>	<small>Use ID number on packaging to assist with correspondence; refer to this label (check box)</small>								
	<input type="checkbox"/> Glacier		<input type="checkbox"/> Madrona		<input type="checkbox"/> Obsidian		<input type="checkbox"/> Pebble		
	Classification: Production Line	Initial	Weathered	Initial	Weathered	Initial	Weathered	Initial	Weathered
	Solar Reflectance	0.25	Pending	0.25	Pending	0.20	Pending	0.25	Pending
Thermal Emittance	0.93	Pending	0.90	Pending	0.93	Pending	0.91	Pending	
Rated Product ID Number	0007		0008		0009		0010		
Licensed Seller ID Number: 1018	<small>CRRC Roof Rating® is a trademark of Cool Roof Rating Agency, Inc. and is not to be reproduced, distributed, or used in any manner without the express written permission of Cool Roof Rating Agency, Inc. The actual effect of solar performance and thermal emittance may vary.</small>								

 <small>COOL ROOF RATING AGENCY</small>	<small>Use ID number on packaging to assist with correspondence; refer to this label (check box)</small>								
	<input type="checkbox"/> Snowcap		<input type="checkbox"/> Snowcap AR						
	Classification: Production Line	Initial	Weathered	Initial	Weathered	Initial	Weathered	Initial	Weathered
	Solar Reflectance	0.28	Pending	0.28	Pending	0.28	Pending	0.28	Pending
Thermal Emittance	0.90	Pending	0.94	Pending	0.94	Pending	0.94	Pending	
Rated Product ID Number	0015		0016						
Licensed Seller ID Number: 1018	<small>CRRC Roof Rating® is a trademark of Cool Roof Rating Agency, Inc. and is not to be reproduced, distributed, or used in any manner without the express written permission of Cool Roof Rating Agency, Inc. The actual effect of solar performance and thermal emittance may vary.</small>								



a division of PABCO building products, LLC

©2010 PABCO® Roofing Products. All trademarks © are registered trademarks. Premier Radiance™ is a trademark of Pacific Coast Building Products, Inc. Printed colors shown in this brochure may vary from actual shingle colors. We recommend color selection be made from actual shingle samples.

PR150a PG 5,000 5/25/10